

UNIVERSITY OF ŽILINA IN ŽILINA  
Faculty of Mechanical Engineering  
Department of Materials Engineering

---



# SEMDOK 2013

18<sup>th</sup> International of PhD. students' seminar

under the auspices of  
prof. Dr. Ing. Milan Sága  
dean of the Faculty of Mechanical Engineering of the University of Žilina in Žilina



Terchová, Slovakia  
30 January – 1 February, 2013

# SEMDOK 2013

18<sup>th</sup> International of PhD. students' seminar

Terchová, Slovakia  
30 January – 1 February, 2013

**Organizing committee:** prof. Ing. Peter Palček, PhD.  
prof. Ing. Radomila Konečná, PhD.  
prof. Ing. Otakar Bokúvka, PhD.  
Ing. František Nový, PhD.  
Mgr. Alena Töröková

<b>Scientific committee:</b>	prof. Ing. Peter Palček, PhD.	(SK)
	prof. Ing. Radomila Konečná, PhD.	(SK)
	prof. Ing. Otakar Bokúvka, PhD.	(SK)
	prof. Ing. Eva Tillová, PhD.	(SK)
	prof. Ing. Mario Guagliano	(IT)
	dr.h.c. prof. Ing. Gianni Nicoletto	(IT)
	dr.h.c. prof. RNDr. Ludvík Kunz, CSc	(CZ)
	prof. Ing. Igor Emri	(SI)
	prof. Ing. Ruzica Nikolic, PhD., M.S., M.Sc.	(RS)
	prof. Dr. János Takács	(HU)
	prof. Dr. Ing. Leszek Dobrzański	(PL)
	prof. Dr. Ing. Stanisław Borkowski	(PL)
	Assoc. prof. Ing. Branislav Hadzima, PHD.	(SK)
	Assoc. prof. Dr. Ing. Robert Ulewicz	(PL)
	Assoc. prof. Dr. Ing. Jacek Seledak	(PL)

## SEMDOK 2013

18<sup>th</sup> International of PhD. students' seminar  
Terchová, 30 January - 1 February, 2013  
UNIVERSITY OF ŽILINA IN ŽILINA, SK



**Reviewers :**

- Belan Juraj
- Bokůvka Otakar
- Borkowski Stanislaw
- Hadzima Branislav
- Konečná Radomila
- Liptáková Tatiana
- Mičian Miloš
- Nový František
- Palček Peter
- Selejdak Jacek
- Tillová Eva
- Ulewicz Robert
- Zatkalíková Viera

**Note:** Authors are responsible for language contents of their papers.

**Name :** SEMDOK 2013, 18<sup>th</sup> International of PhD. students' seminar

**Printed :** EDIS – Editing Centre ŽU, University of Žilina in Žilina,  
Slovak republic, 2013

**Prepared :** University of Žilina in Žilina, Slovakia  
Faculty of Mechanical Engineering  
Department of Materials Engineering

**Design :** Mgr. Alena Töröková

**ISBN 978-80-554-0629-9**



## INFLUENCE OF LUBRICANTS ON THE MULTIPHASE IRONING PROCESS

Milan Djordjević<sup>1</sup>, Sbrislav Aleksandrović<sup>1</sup>, Vukić Lazić<sup>1</sup>, Milentije Stefanović<sup>1</sup>,  
Ružica R. Nikolić<sup>1,2\*</sup>, Dušan Arsić<sup>1</sup>

<sup>1</sup> Faculty of Engineering, University of Kragujevac, Serbia.

<sup>2</sup> Faculty of Civil Engineering, University of Žilina, Slovak Republic.

\* Corresponding e-mail address: ruzicarnikolic@yahoo.com

### Abstract

*In this paper are presented results of experimental investigations of the type of lubricants influence on the ironing process. The tribological model was adopted, based on sliding of the metal strip between the two contact elements. Variations of the tensile force, contact pressure and the friction coefficient were investigated for each of the applied lubricants, in the three-phase ironing process, at constant sliding velocity. The objective of these investigations was to compare the applied lubricants and to estimate their quality from the aspect of their applicability in the ironing process.*

**Keywords:** Ironing, Tribological model, Friction coefficient, Contact pressure, Tensile force.

### 1. Introduction

The ironing process in cold conditions is frequently characterized by high contact pressures and local load of the tool, especially in the case of the multi-phase process. In such conditions, the lubricant has the decisive influence on plastic forming. Absence of lubricant would cause the direct contact of the machined piece and the tool, what would significantly disrupt the stability of the forming process. Lubrication, as a measure of reducing the damaging influence of friction, enables increase of the deformation and deep drawing degree, [1]. Application of lubricants eliminates or decreases the harmful phenomenon of galling, [2], wear of the tool's working surfaces and improves the quality of the machined piece surfaces.

Based on the adopted tribological model [3, 4], the original device was developed, based on sliding of the thin sheet samples between the side elements (die) in three phases. The contact surfaces between the sample and the die were separated by the layer of lubricant. The three types of lubricants were applied: a) lubricant in the form of the zinc phosphate coating with oil, b) lubricating grease based on molybdenum-disulphate and c) oil for deep drawing. For each type of lubricants and the blank holding force, the measurement of the tensile force was performed.

### 2. Experimental device and the tribological model

For experimental investigations a device was constructed which models the symmetrical contact of the thin sheet with the die during the ironing process [3, 4] (Fig. 1). The metal strip is being placed into the holding jaw 12. The jaw with the sample is moving from the bottom towards the top, by the mechanical part of the device. The sample is being acted upon by the side elements 10 and 11, which simulate the die and perform the ironing. The moving sliding element 10 is placed into the holder with a T-groove 9, which is moving with piston 8 and hydro-cylinder 7. The sliding element 11 is fixed. During the ironing process the recording of the tensile force is being done at over the total length of the punch travel of approximately 60 mm, by the corresponding measuring chain.









